



MAX II SEAT MOUNT

IMPORTANT INFO

- Meets FMVSS213 when used with Max 2 Vest.
- Use only with EZ-ON Vest. Compatible Vest include: MAX II
- Use on school bus seats that have entry between the seat bottom and seat back.
- Passengers seated behind occupants with MAX II seat Mount must be wearing a seatbelt, a transportation vest, or must be unoccupied.
- Register this Seat Mount to be notified of a safety recall.

WARRANTY

EZ-ON Products stands behind the products we make. Warranty covers any defects in material or workmanships under normal use during the warranty period. We will repair or replace product defects for 1 year from manufacturer date.

WARNING

Death or serious injury can occur if manufacturer's instructions are not followed correctly. All EZ-ON products are dynamically tested to meet NHTSA standards. Please follow washing instructions on product tag. Replace product if it is damaged, frayed, or has been in a crash. Recommended replacement after six years. EZ-ON Products are not liable for injury if these recommendations are not followed.

EMERGENCY RELEASE PROCEDURE

When evacuating the passenger in a safety vest, the vest webbing is never cut. Three cuts of the portable seat mount webbing below the buckle and adjusters will allow the passenger to evacuate the bus wearing the safety vest.



**100 SCBC
EZ-ON Safe Cut
Belt Cutter**





MAX II SEAT MOUNT

INSTALLATION INSTRUCTIONS



1. Unlock seat and lift up.

2. Hang shoulder strap from top of seat.

SECURING MOUNT STRAP

3. Wrap mount strap around seat

4. Connect push button. Face of push button must be against bus seat back.

5. Tighten webbing by pulling down on the excess webbing.

6. Webbing must be tight enough to create a crease on the bus seat top.

7. Close seat bottom, with hip straps on the seat bottom

8. Lock seat bottom in place.

9. Properly seat passenger (hips low against the back of the seat and shoulders flush to the seat).

10. Attach hip level tether hooks to the hip level D-rings on EZ-ON Vest.

*Be sure that passenger has a properly fitted vest.

11. Tighten hip straps by pulling on the webbing through the tilt adjuster on the back side of the seat.

*Goal is to have the hip level d-rings to sink into the seat bite.

12. Loop shoulder strap through D-ring at shoulder level

13. Hook shoulder strap to D-ring on the back of the seat.

14. Tighten shoulder strap by pulling on the loose webbing.

*Repeat steps 12 – 14 for second shoulder strap.