



**EZ-ON
PRODUCTS**

86Y-CAR CAM

INSTALLATION INSTRUCTIONS

IMPORTANT INFO

- Meets FMVSS213
- Installation of 86Y requires the use of a tether anchor.
 - Use the vehicle's factory-installed (or EZ-ON's tether hardware kit) tether anchor.
 - If the vehicle manufacturer states a tether anchor weight limit and the child exceeds that weight, install/use EZ-ON's tether hardware.
 - Instructions for EZ-ON's hardware kit are included on the kit's assembly bag; video instructions are also available at ezonpro.com.
- 100H (Hardware Kit) not included.
 - If you know you will need the 100H, it must be requested at the time of purchase. However, it can be purchased on its own if you already have the product.
- Passengers using EZ-ON transportation vest systems 86Y:
 - Must weigh over 66 lbs.
 - Must utilize a seat belt, per vest instructions.
 - Should not ride in a booster seat.
- When heavy clothing, like winter jackets, are worn, the vest must be worn underneath.
- Recommended replacement 6 years after date of manufacturing.



For passengers over 66 lbs



WARNING

Death or serious injury can occur if manufacturer's instructions are not followed correctly. Read below warning information for replacement recommendations.



REGISTER

Register this transportation vest to be notified of a safety recall.



WARRANTY


EZ-ON Products stands behind the products we make. Warranty covers any defects in material or workmanship under normal use during the warranty period. We will repair or replace product defects for 1 year from manufacturer date.

WARNING: All EZ-ON products are dynamically tested to meet NHTSA standards. Replace product if it is damaged, frayed, or has been in a crash. Recommended replacement period is six years. EZ-ON Products are not liable for injury if these recommendations are not followed.

CUT ALONG DOTTED LINE FOR EMERGENCY RELEASE



100 SCBC
EZ-ON Safe Cut
Belt Cutter



605 Commerce Way West
PO Box 660
Jupiter, FL 33458

561.747.6920
cs@ezonpro.com

EZONPRO.COM



**EZ-ON
PRODUCTS**

86Y CAR CAM

INSTALLATION INSTRUCTIONS

SCAN CODE TO VIEW VIDEO
INSTRUCTIONS & MORE



Check the vehicle owner's manual to locate factory installed tether anchor bracket.
43YC tether strap can be turned one half twist to snap on difficult anchor locations.



1. Locate the tether anchor bracket.



2. Connect tether hook to tether anchor bracket directly behind passenger. Twenty degrees from "Y" center is acceptable.



3. Place the Y-bridge on the seat top. Rest black shoulder straps on the front of the seat.



4. Adjust tilt lock adjuster to remove excess webbing so Y-bridge sits on seat top.



5. Place the adjustable belt straps over each shoulder of the passenger.



6. Allow the belt loop ends to lay on the passenger's lap.



7. Thread the vehicle seat belt across the lap and through each belt loop.



8. First adjust the gray crotch strap from the top of the seat, by pulling on the loose webbing.



9. To adjust the shoulder vest straps, slide the webbing up or down through the adjuster. Keep both adjusters as close to the shoulders as possible.



10. Secure the chest clip keeping the clip below the vest adjusters at arm pit level.

WARNING: Do not shorten the shoulder straps too much. This can cause the lap belt to be over the stomach causing injury.

Exceptional Safety Solutions for Transporting Children and Adults.